

TeleMoment

Reliable Critical Power

Uninterruptible Power Supply RM11 Rackmount Series



Ranging from 1KVA to 10KVA, is double conversion online rack UPS with fully DSP controlled technology. The single phase of 6-10KVA UPS applies the advanced 3-level technology, achieving an efficiency up to 95%. With its compact design of high power density (kW=kVA) in 2U height, HR11 series make it ideal choice for computers, telecommunication equipment and other sensitive devices.

Technical Specifications

**Double Conversion
True Online UPS**

**Rackmount/Tower
convertible form factor**

**Easy battery
replacement and
expansion**


**Web enabled via
optional SNMP card**

**PCB tropicalisation for
tough operation
environment**

Extra options:

- External bypass
- SPD
- PDU
- Rackmount cabinet
- Tailored made batt. cabinet

MODEL	RM1101S	RM1102S	RM1103S	RM1106XS	RM1110XS
	RM1101L	RM1102L	RM1103L	RM1106XL	RM1110XL
Capacity	1kVA	2kVA	3kVA	6kVA	10kVA
Input voltage range	110VAC-288VAC				
	100% load@>176VAC; 80% load@>154VAC 70% load@>132VAC; 50% load@>110VAC			100% load@ > 176VAC; 90% load@ > 160VAC 80% load@ > 140VAC; 60% load@ > 110VAC	
Input frequency	40-70Hz				
Input PF	≥0.97			≥0.99	
Voltage regulation	±1 %				
Output frequency	50/60Hz				
Output PF	0.9			1.0	
Overload capability (Inverter mode)	105%-130%: to bypass 1 min; 150%: to bypass after 30 sec			110%:for 10 min ;125%:for 1min ; 150%:for 30 sec	
Overload capability (Battery mode)	105%-130%: shutdown after 10 sec; 150%: shutdown after 5 sec			110%: shut down after 1 min; 130%:shut down after 10 sec; >130%: shut down after 200 ms	
Crest factor	3:1				
Efficiency	87%	91%	90%	95%	
Display	LED+LCD				
Battery voltage	36VDC	72VDC	96VDC	192VDC	
Battery type/number	12V,7Ah*3	12V,7Ah*6	12V,7Ah*8	12V,7Ah*16	12V,9Ah*16
	External				
Interface	RS232,SNMP				
Optional	USB, SNMP, Dry contacts			USB, SNMP, ECO kit, Dry contacts, Battery cabinet	
Operation temperature	0-40°C				
Relative humidity	0-95%(non-condensing)				
W*D*H(mm)	440*430*86	440*480*173	440*480*173	440*660*173	
	440*430*86	440*480*86	440*480*86	440*550*86	
Weight(kg)	11.5	25	31	59	67
	7	8	9.5	17.5	20.5



TeleMoment

Astrid Electronics HK Limited

Flat C-D, 9/F, Lucky Factory Building,
63-65 Hung To Road, Kwun Tong,
Kowloon, Hong Kong.

Tel: +852 3427 2600

Fax: +852 2173 5111

www.telemoment.com

www.astrid.hk Email: info@astrid.hk

